

## SPECIFICATION FOR APPROVAL

### 產品確認書/製品仕様書

FILE SERIAL NO./檔序號:

XSG20230722007-T01

CUSTOMER / 客 戶:

ARTICLE / 品 名:

SWITCHING POWER SUPPLY

MODEL NO. / 機種型號:

XSG1201200UK

PARAMETER / 規 格:

12V1.2A

CERTIFICATE/認證:

CB, UKCA CE

ISSUE DATE / 發行日期:

2023/7/25

**Please to sign back after you confirm**

**承認書確認後請回簽一份**

この仕様書をご確認とご署名の上、対象の営業窓口にご返信いただきますよう宜しくお願い致します。

| CUSTOMER AUTHORIZED<br>客戶確認 |            |             |
|-----------------------------|------------|-------------|
| Approved by                 | Checked by | Prepared by |
|                             |            |             |

| SUPPLIER AUTHORIZED<br>供方確認 |            |             |
|-----------------------------|------------|-------------|
| Approved by                 | Checked by | Prepared by |
| 李麗敏                         | 賀子豐        | 張文娟         |

\*感謝您的支持，我們十分珍惜每次合作機會

\*Thank you for your support, we will treasure the opportunity to cooperate with you

| Rev.版本 | Description of change/ 變更內容描述 |           | Changed Date<br>日期 | Approved |
|--------|-------------------------------|-----------|--------------------|----------|
|        | Before(變更前)                   | After/變更後 |                    |          |
| A      | Original Release(初次發行)        |           | 2023/7/25          | 李麗敏      |
|        |                               |           |                    |          |
|        |                               |           |                    |          |
|        |                               |           |                    |          |
|        |                               |           |                    |          |



**\* Make practical and safe power supply, Be enterprise with honesty and responsibility**

\* 提供實用安全的電源，做誠信負責的企業

\* 実用的、安全な電源を提供し、誠実と信用、責任を持つ企業。

# Table of Content(目錄)

[illegible]

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 2/9 |
|---------|---|------|-----|

## ELECTRICAL PERFORMANCE / 電器性能

### 1.SAFETY STANDARD / 安規標準

- 1.1 The green mode power supply shall be certified by the following international regulatory standards:充電器應符合下列的國際標準：

| Certificate<br>證書                              | Country<br>國家    | Standard/安規標準                            | Certificate<br>證書                | Country<br>國家 | Standard/安規標準                                    |
|------------------------------------------------|------------------|------------------------------------------|----------------------------------|---------------|--------------------------------------------------|
| <input type="checkbox"/> UL/cUL                | USA/CA<br>北美     | UL62368-1;                               | <input type="checkbox"/> FCC     | USA           | FCC Part 15<br>Sub-part B                        |
| <input checked="" type="checkbox"/> LVD / UKCA | Eu / UK<br>歐盟 英國 | EN62368 BSEN 62368                       | <input type="checkbox"/> CE      | Europe<br>歐洲  | EN55032;EN55035;<br>EN55024;EN61000;<br>EN55022; |
| <input checked="" type="checkbox"/> CB         | Global<br>全球     | IEC62368;IEC61558;<br>IEC60335: IEC61010 | <input type="checkbox"/> KC      | Korea<br>韓國   | K60950-1                                         |
| <input type="checkbox"/> PSE                   | Japan<br>日本      | J60335-1(H27)<br>J60335-2-29(2019)       | <input type="checkbox"/> SAA/RCM | AU 澳洲         | AS/NZS 62368.1:2018                              |
| <input type="checkbox"/> GS                    | Germany<br>德國    | EN 62368-1:EN61558<br>EN 60335           | <input type="checkbox"/> CCC     | CN<br>中國      | GB 17625.1-2012;GB<br>4943.1-2011                |

### 2.INPUT FEATURE / 輸入特性

- 2.1 INPUT VOLTAGE RANGE: 90Vac to 264Vac. 輸入電壓範圍可以從90Vac到264Vac.
- 2.2 RATED INPUT VOLTAGE: 100Vac to 240Vac. 額定輸入電壓從100Vac到240Vac.
- 2.3 INPUT FREQUENCY RANGE: 47Hz to 63Hz. 輸入頻率範圍從47Hz到63Hz.
- 2.4 INPUT CURRENT: 0.6A max.&100-240Vac. 最大輸入電流0.6A (輸入條件100-240Vac)
- 2.5 INRUSH CURRENT: 35A max. at 100-240Vac input for a cold start at 25℃.在准開機條件下，最大浪湧電流不超過35A (輸入條件100-240Vac).
- 2.6 EFFICIENCY: higher than 83.9% at 100-240Vac input and output full load. 效率高於83.9% (輸入100-240Vac 和輸出滿載條件) .
- 2.7 No-Load Input Power Dissipation/輸入空載功率損耗：Input 115Vac or 230Vac,output no load, the input power loss is less than 0.1W. 輸入115/230V交流，在空載時，輸入功耗小

### 3.OUTPUT/輸出特性

| RATED OUTPUT / 額定輸出         | SPEC. LIMIT / 規格限定 |            | REMARK / 備註                                       |
|-----------------------------|--------------------|------------|---------------------------------------------------|
|                             | Min. value         | Max. value |                                                   |
| Output regulation / 輸出電壓規格  | 11.4VDC            | 12.6VDC    | 12V±5%                                            |
| Output load / 輸出負載規格        | 0.0A               | 1.2A       | Peak Current:1.44A                                |
| Ripple and Noise / 輸出紋波及雜訊  | —                  | <100mVp-p  | 20MHz Bandwidth 10uF Ele.<br>Cap.& 0.1uF Cer. Cap |
| Output Overshoot / 輸出過沖幅度   | —                  | 10%        |                                                   |
| Line regulation / 電壓調整率     | —                  | ±1%        |                                                   |
| Load regulation / 負載調整率     | —                  | ±3%        |                                                   |
| Turn-on delay time / 開機延遲時間 | —                  | 3000mS     |                                                   |
| Hold up time / 關機維持時間       | 10mS               | —          | Input voltage:115Vac                              |
|                             | 20mS               | —          | Input voltage:230Vac                              |

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 3/9 |
|---------|---|------|-----|

## ELECTRICAL PERFORMANCE / 電器性能

### 4.4 IELECTRIC WITHSTANDING STRENGTH(HI-POT) / 絕緣介電強度 (耐壓)

Primary to Secondary AC3000V, 10mA, 1 minute for type test, 3 second for production.  
一次側對二次側: AC3000V, 10mA標準測試1分種, 量產測試3秒鐘.

## 5.PROTECTION FEATURE / 保護特性

### 5.1 OVER—CURRENT PROTECTION / 過電流保護:

The green mode power supply shall be hiccup when any output operating in overload condition(set@ Max load 120~180% ) under any line condition for an indefinite period of time. The power supply shall be self — recovery when the fault condition is removed. 在任何時候任何輸入條件, 當輸出操作在超載條件最大電源的 (120~180% ) 時, 電源供應器將進入打嗝模式, 當故障被移走後, 電源要能自動恢復到正常。

### 5.2 SHORT—CIRCUIT PROTECTION / 輸出短路保護:

The power supply shall be hiccup and no damage shall occur when any output operating in a short circuit condition under any line condition for an indefinite period of time. The power supply shall be self—recovery when the fault condition is removed. 在任何時候, 任何輸入條件下, 當輸出操作在短路情況下, 電源供應器將進入打嗝模式, 當故障消失後, 電源要能自動恢復正常。

## 6.ENVIRONMENTAL CONDITIONS / 環境條件

### 6.1 OPERATING / 操作條件:

The power supply shall be capable of operating continuously in any mode without performance deterioration in the following environmental conditions. 在下列環境條件下, 電源供應器要能夠連續操作在各種模式, 且不能造成性能的退化。

6.1.1 Operating Temperature: -20℃~40℃ 工作溫度: -20℃~40℃

6.1.2 Relative Humidity: 10%~90% 相對濕度: 10%~90%

6.1.3 Vibration: 1.0mm, 10—25Hz, 15 minutes per cycle for each axis (X, Y, Z)

6.1.4 Cooling: The power supply will operate with convection cooling. Blocking of vents must not cause damage to the power supply. 電源供應器將操作在對流冷卻的環境下, 即使將通風口阻塞電源也不允許有任何損傷發生。

### 6.2 NON—OPERATING / 非操作條件:

The power supply shall be capable of withstanding the following environmental conditions extended periods of time, without sustaining electrical or mechanical damage and subsequent operational deficiencies.

電源供應器要能夠長期的經受下列的環境條件, 且不允許有電氣級機械方面的損傷和併發的操作的缺失

6.2.1 Storage Temperature: -30℃~70℃ 儲存溫度: -30℃~70℃

6.2.2 Relative Humidity: 10%~90%相對濕度: 10%~90%

6.2.3 Color of case and cable / 外殼及線材顏色: Black / 黑色

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 4/9 |
|---------|---|------|-----|

---

## ELECTRICAL PERFORMANCE / 電器性能

### 6.2.4 Vibration and Shock / 振動和衝擊

The power supply shall be designed to withstand normal transportation vibration per MIL—STD—810D, method 514 and procedures X, as it is mounted in the chassis assembly and packed for shipping.

電源供應器出貨的包裝設計，均要能承受正常運輸的振動，並符合MIL—STD—810D方法514 和程式 X。

## 7. EMC STANDARDS / 電磁相容性標準

### 7.1 EMI STANDARDS / EMI 標準

The power supply met the radiated and conducted emission requirements for FCC CLASS B, EN55032 CLASS B.

本電源供應器符合輻射及傳導要求，滿足FCC CLASS B, EN55032 CLASS B.

### 7.2 EMS STANDARDS / EMS 標準

The power supply shall meet the following EMS standards: 本電源供應器滿足下列EMS標

7.2.1 EN61000-4-2: 2009 / A1: 1998 Electrostatic Discharge(ESD)

7.2.2 EN61000-4-3: 2010 / A1: 1998 Radiated Electromagnetic Fields(RS)

7.2.3 EN61000-4-4: 2012 Electrical Fast Transient / Burst(EFT)

7.2.4 EN61000-4-5: 2014 Lighting Surge Attachment. Line to Neutral: 2KV

## 8 RELIABILITY AND QUALITY CONTROL / 可靠性及品質控制

### 8.1 BURN—IN / 老化

The power supply shall undergo a minimum of 4 hours Burn—In test under full load at 40°C~±5°C

電源應在40°C~±5°C和滿載條件下老化4 小時。

### 8.2 COMPONENT DERATING / 元件溫度要求

Semiconductor junction temperatures shall not exceed the manufacturer's maximum thermal rating. 半導體結溫不允許超過其製造商要求的最大溫度值。

## 9. WEIGHT / 重量

The weight of the power supply shall be about 80g 電源的重量大約為80g。

## 10. MECHANICAL REQUIREMENT / 結構參數

The power supply size: L63.9\*W37.7\*H27.9mm. 外殼尺寸: L63.9\*W37.7\*H27.9mm

## 11. INSULATION RESISTANCE / 絕緣阻抗

Input to output: 50M OHM(500VDC) 輸入對輸出50兆歐姆 (500VDC)

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 5/9 |
|---------|---|------|-----|

## ELECTRICAL PERFORMANCE / 電器性能

### 12.LEAKAGE CURRENT / 漏電流


The leakage current shall be **less than 0.25mA for class II** when power supply is operated maximum input voltage and maximum load. 當電源供應器操作在最大輸入及最大負載情況下，其漏電流應 **小於0.25mA, 滿足class II等級**。

### 13.MAJOR MEASURE EQUIPMENT / 主要測量設備; VERIFIED BY THE THIRD LAB/外校

- A AC SOURCE / AC變頻電源: 固緯/GWINSTEK APS-7100E,校準頻次: 1次/年 ☐ ✓
- B DIGITAL POWER METER / 數字功率計功率儀: 固緯/GWINSTEK GPM-8213,校準頻次: 1次/年 ☐ ✓
- C ELECTRONIC LOAD / 開編程電子負載儀: 美爾諾/MAYNUO M9713,校準頻次: 1次/年 ☐ ✓
- D OSCILLOSCOPE / 存儲示波器: 泰科/TEKTRONIX TBS1102B,校準頻次: 1次/年 ☐ ✓
- E DIGITAL MULTIMETER / 數字式萬用表: 福祿克(FLUKE) F12E+校準頻次: 1次/年 ☐ ✓
- F DC POWER / 直流電源: 麥創 (MATRIX) MPS-6030D校準頻次: 1次/年 ☐ ✓
- G HIPOT AND INSULATION RESISTANCE TESTER / 耐壓安規測試儀:  
固緯/GWINSTEK GPT-9803 ,校準頻次: 1次/年 ☐ ✓
- H NSULATION RASISTANCE TESTER / 絕緣電阻表: YD2681A,校準頻次: 1次/年 ☐ ✓
- I MULTI CHANNEL TEMPERATURE SENSOR / 多路溫度測試儀  
艾維泰科/IVYTECH IV380-16校準頻次: 1次/年 ☐ ✓

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 6/9 |
|---------|---|------|-----|

## DC CORD / 輸出 線材




### Cable Specification/線材規格

**UL2468 Flat Wire, 22AWG\*2C L=1200MM Black 80°C, 300V**

| Item No | Part Name ( 部件名稱 )             | Description ( 描述 )         |
|---------|--------------------------------|----------------------------|
| A       | Length of DC cord(DC線長度)       | 1.2M                       |
| B       | Size of DC connector ( DC頭尺寸 ) | 5.5*2.1*10mm直頭內正外負, 音叉帶溝槽。 |
| C       | Length of coil ( 線包長度 )        | 70MM±10                    |
| D       | SR NO(線卡編號)                    | XYX-XL009                  |
| E       | Length of inlet wire ( 出線長度 )  | 30MM±1                     |
| F       | Tinned length ( 吃錫長度 )         | 4MM±1                      |

|                |          |             |            |
|----------------|----------|-------------|------------|
| <b>EDITION</b> | <b>A</b> | <b>PAGE</b> | <b>7/9</b> |
|----------------|----------|-------------|------------|

## PRODUCT OUTLINE DIMENSION / 產品外觀尺寸



**Material/材料:** PC


**Brand/品牌:** SABIC / 沙伯

**Fireproof Class/防火等級:** UL94V-0

**Color/顏色:** Black/黑色

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 8/9 |
|---------|---|------|-----|

RATING LABEL / 銘牌



标贴仅供参考

Print/印刷 ☐

☒ Laser Carving/鐳雕

- 1.Silver text on black background黑底銀字
- 2.Material: PET 底材為消銀龍.
- 3. Clear Printing, Wipe Resistance絲印清晰，耐擦拭.
- 4.Gum Permanent永久背膠.
- 5.Meet Requirements of Environmental Protection符合環保要求

|         |   |      |     |
|---------|---|------|-----|
| EDITION | A | PAGE | 9/9 |
|---------|---|------|-----|