



Dongguan Anci Electronic Technology Co., Ltd.

Add.: 1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan Lake

Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

Tel: 86 -769 -8507 5888 Fax: 86 -769 -8507 5898 Web: www.anci.com

ATTESTATION OF CONFORMITY

Attestation No. 20AE05408A015

This Attestation of Conformity is hereby issued to the product designated below

Report No. : EA2005408A15001
Applicant : Xinsu Global Electronic Co., Limited
Address : Unit 2508A, 25/F, Bank of America Tower, 12 Harcourt Road
Central, HONG KONG
Manufacturer : Xinsu Global Electronic Co., Limited
Address : Unit 2508A, 25/F, Bank of America Tower, 12 Harcourt Road
Central, HONG KONG
Description of Product : SWITCHING POWER SUPPLY/CHARGER
Model No. : XSGxxxxyyy L3 , XSGxxxxyyyAU L3,
XSExxxxyyy L3, XSExxxxyyyAU L3 ,
XSECxxxxyyy L3, XSECxxxxyyyAU L3
(xxx and yyy are variables, see next page for details)
Input Rating : 100-240VAC, 50/60Hz, 0.6A Max
Output Rating : 4.2-48.0Vdc, 0.1-4.0A, 30.0W Max
Test Standards : AS CISPR 11: 2017+A1:2020

This device in conformance with AS CISPR 11: 2017+A1:2020 Industrial, scientific and medical equipment.

Test Laboratory


Alan He
Director
Date of Issue: June 28, 2021

This Attestation of Conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the whole production and other relevant Directives have to be observed.



Dongguan Anci Electronic Technology Co., Ltd.

Add.: 1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan Lake

Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

Tel: 86 -769 -8507 5888 Fax: 86 -769 -8507 5898 Web: www.anci.com

ATTESTATION OF CONFORMITY

Certificate No.: 20AE05408A015

Attachment

Model list:

Model	Rated output voltage (VDC)	Rated output current (A)	Max. rated output power (W)	Transformer
XSGxxxxxyyyAU L3, XSGxxxxxyyy L3, XSExxxxxyyy L3, XSExxxxxyyyAU L3, XSECxxxxxyyyAU L3, XSECxxxxxyyy L3	4.2-6.9	0.01-4.00	20.0	TR-030-T01
	7.0-9.0	0.01-3.00	22.5	
	10.0-12.0	0.01-2.50	30.0	TR-030-T02
	12.1-12.6	0.01-2.47	30.0	
	12.8-17.0	0.01-2.34	30.0	
	18.1-20.0	0.01-1.50	30.0	TR-030-T03
	21.0-36.0	0.01-1.42	30.0	
	36.1-48.0	0.01-0.80	30.0	TR-030-T04

Note:

1. xxx=042-480, represents for the rated output voltage from 4.2VDC to 48.0VDC;
2. yyy=0010-4000, represents for the rated output current from 0.01A to 4.0A.

Differences between all models are see below table for details:

Model	Supply connecting	PCB layout type	Enclosure type
XSGxxxxxyyyAU L3	Fixed plug	Type A	Direct plug-in
XSGxxxxxyyy L3, XSExxxxxyyy L3	Detachable plug		Direct plug-in
XSECxxxxxyyyAU L3, XSExxxxxyyyAU L3	Non-detachable power cord	Type B	Desk-top
XSECxxxxxyyy L3	Appliance inlet		Desk-top