



Product Service

Attestation of Conformity

No. N8A 094747 0044 Rev. 00

Holder of Certificate: **Xinsu Global Electronic Co., Limited**
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG

Product: **Switching power supply unit
(SWITCHING POWER SUPPLY/CHARGER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 6824020000501

Date, 2021-04-08

(Alex Kong)

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 094747 0044 Rev. 00

Model(s):

XSGxxxxxyyyzz L3, XSGxxxxxyyy L3,
XSExxxxxyyy L3, XSExxxxxyyyzz L3,
XSECxxxxxyyyzz L3, XSECxxxxxyyy L3
(xxx, yyy and zz are variables, xxx=042-480,
represents for the rated output voltage from 4.2VDC
to 48.0VDC; yyy=0010-4000, represents for the
rated output current from 0.01A to 4.0A; zz=EU, UK,
stands for different national plug; EU means European
plug, UK means Britain plug.)

Brand:

Xinsu Global

**Parameters:**

Rated Input: 100-240VAC, 50/60Hz, 0.6A Max

Rated Output: See below table for details

Protection Class: II

Degree of Protection: IP20



Product Service

Attestation of Conformity

No. N8A 094747 0044 Rev. 00

Model	Rated output voltage (VDC)	Rated output current (A)	Max. rated output power (W)
XSGxxxxxyzz L3, XSGxxxxxy L3, XSExxxxxy L3, XSExxxxxyzz L3, XSECxxxxxyzz L3, XSECxxxxxy L3	4.2-6.9	0.01-4.00	20.0
	7.0-9.0	0.01-3.00	22.5
	10.0-12.0	0.01-2.50	30.0
	12.1-12.6	0.01-2.47	30.0
	12.8-17.0	0.01-2.34	30.0
	18.1-20.0	0.01-1.50	30.0
	21.0-36.0	0.01-1.42	30.0
	36.1-48.0	0.01-0.80	30.0

**Tested
according to:**

EN 61010-1:2010/A1:2019

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.