

CERTIFICATE OF CONFORMITY

Electromagnetic Compatibility (EMC) Directive 2014/30/EU

This Certificate of Conformity is hereby issued to the product designated below:

Certificate No......: 25EP02107E04
Report No......: EP2502107E04
Date Issue......: 2025-09-21
Applicant's name.....: Xinsu Global Electronic Co., Limited
Address.....: Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road Central, HONG KONG
Manufacturer's name.....: Xinsu Global Electronic Co., Limited
Address.....: Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road Central, HONG KONG
Product Description.....: SWITCHING POWER SUPPLY /CHARGER
Model(s)/Type References : XSGxxxxxyyyz L3, XSGxxxxxyyy L3, XSExxxxxyyy L3 , XSExxxxxyyyz L3 , XSECxxxxxyyyz L3 , XSECxxxxxyyy L3 (xxx, yyyy and zz are variables, see appendix for details)
Parameters.....: Input: 100-240V~, 50/60Hz, 0.6A Max.
Output: See appendix for details.
Standard(s).....: EN 55011:22016+A1:2017+A11:2020+A2:2021
EN IEC 61000-6-1:2019
EN IEC 61000-3-2:2019+A1:2021+A2:2024
EN 61000-3-3:2013+A1:2019+A2:2021

On the basis of the referenced test report(s), sample(s) tested of the above product have been found to comply with the standards harmonized with the directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it(them).

Once compliance with all product relevant CE mark directives are verified, including any relevant e.g. risk assessment and production control, the manufacturer may indicate compliance by signing a Declaration of Conformity themselves and applying the mark to products identical to the tested sample(s).

Approved By

Eric Liu
Director of engineering department

CERTIFICATE OF CONFORMITY

Electromagnetic Compatibility (EMC) Directive 2014/30/EU

Appendix of Certificate No.: 25EP02107E04

Model list:

Model	Output voltage (Vdc)	Output current (A)	Max. Output Power (W)	Transformer (T1) type
XSGxxxxxyyyzz L3, XSGxxxxxyyy L3, XSExxxxxyyy L3 , XSExxxxxyyyzz L3 , XSECxxxxxyyyzz L3 , XSECxxxxxyyy L3	4.2-6.9	0.01-4.00	20.0	TR-030-T01
	7.0-9.0	0.01-3.00	22.5	
	9.1-12.0	0.01-2.50	30.0	TR-030-T02
	12.1-12.6	0.01-2.47	30.0	
	12.7-17.0	0.01-2.34	30.0	
	17.1-20.0	0.01-1.50	30.0	TR-030-T03
	20.1-36.0	0.01-1.42	30.0	
	36.1-48.0	0.01-0.80	30.0	TR-030-T04

-xxx=042-480, indicates rated output voltage from 4.2VDC to 48.0VDC;
-yyyy=0010-4000, indicates rated output current from 0.01A to 4.0A;
-ZZ=EU, UK, indicates different mains plug; EU=European plug, UK=Britain plug

