

ATTESTATION OF CONFORMITY

No. 24AS110005S368A001

The submitted sample of below equipment has been tested in according to EC Council Directive of 2014/35/EU with the following standards. The test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the principal protection requirement of the EC Council Directive of 2014/35/EU.

Report No. : S01A24110005P00101

Applicant: Xinsu Global Electronic Co.,Limited

Address : Unit 2508A 25/F Bank of America Tower 12 Harcourt Road Central HK

Manufacturer : Xinsu Global Electronic Co.,Limited

Address : Unit 2508A 25/F Bank of America Tower 12 Harcourt Road Central HK

Description of Product: SWITCHING POWER SUPPLY/CHARGER

Model No. : See page 2 for details

Trade Mark : Xinşû Global®

Input Rating : 100-240VAC or 200-240VAC, 50/60Hz, 2.5A or 3.0A Max

Output Rating : See page 2 for details

Test Standards : EN 62368-1:2014+ A11:2017

After preparation of the necessary technical documentation as well as the EU declaration of conformity, the CE marking as below can be affixed on the product if all relevant effective EU-directives or regulations related to CE marking have been complied with. The EU declaration of conformity is issued under the sole responsibility of the applicant or manufacturer.

Test Laboratory

Victor Yde

Victor Xie Director

Date of Issue: November 11, 2024

This attestation of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the production of the products.

Guangdong GTG Testing Technology Co., Ltd.

Add: 1-2/F., Building Agand 1/F., Building B, No.11 & Room 102, Unit 1, and Room 101 Unit 2, Building 1, 20.9, Zongbu 2nd Road; Songshan Lake High-Tech Industrial Development Zone, Congguan, Guangdong, Shira.

Web: www.gtggroup.com Fel: 86-4

Tel: 86-4007558988



No. 24AS110005S368A001

Model List as below

Model	Output voltage	Output current	Max. Output	Transformer
	(Vdc)	(A)	Power (W)	
XSECxxxyyyy, XSGxxxyyyy, XSExxxyyyy, XSECxxxyyyyy, XSGxxxyyyyy, XSExxxyyyyy,	12.0	0.01-12.0	144.0	TR-180-T1x ("x" =
	12.1-23.9	0.01-10.0	168.0	A-Z, 0-9 or blank, for
				marketing purpose)
	24.0-42.0	0.01-8.33	210.0	TR-180-T2x ("x" =
XSECxxxyyyyzz, XSGxxxyyyyzz,				A-Z, 0-9 or blank, for
XSExxxyyyyzz,				marketing purpose)
XSECxxxyyyyyzz, XSGxxxyyyyyzz,				
XSExxxyyyyyzz				

Remark:

- 1. xxx=120-420 stands for rated output voltage range from 12.0-42.0VDC with step of 0.1V.
- 2. yyyy=0010-9990 stands for rated output current range from 0.01-9.99A with step of 0.01A.
- 3. yyyyy=10000-12000 stands for rated output current range from 10.0-12.0A with step of 0.01A.
- 4. zz=with non-detachable power supply cord,EU or UK, stands for direct plug-in plug

type; EU means Europe plug, UK means Britain plug.

Guangdong GTG Testing Technology Co., Ltd.

Add: 1-2/F., Building Acand 1/F., Building B, Norl 1 & Room 102, Unit 1, and Room 101 Unit 2, Building 1, 20.9, Zonghu 2nd Road; Songshan Lake High-Tech Industrial Development Zone, pongguan, Guangdong, Shira.