

Attestation of Conformity

No. N8A 094747 0024 Rev. 00

Holder of Certificate: Xinsu Global Electronic Co., Limited

Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road

Central HONG KONG

Product: Switching power supply unit


(SWITCHING POWER SUPPLY)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance.

It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 652501905001

Date, 2019-11-07



Page 1 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.







Attestation of Conformity

No. N8A 094747 0024 Rev. 00

XSGxxxyyyy, XSGxxxyyyyzz, XSExxxyyyy, Model(s):

XSExxxyyyyzz, XSECxxxyyyy, XSECxxxyyyyzz, XSGxxxyyyyy, XSGxxxyyyyyzz, XSExxxyyyyy, XSExxxyyyyyzz, XSECxxxyyyyy, XSECxxxyyyyyzz

(See below table for details)

Xinsu Global **Brand:**



Parameters:

Rated Input: 100-240VAC, 50/60Hz, 3.0A Max Rated Output: See below table for details

Protection Class: II Degree of Protection: IP20

Model No.	Rated output voltage (VDC)	Rated output current (mA)	Max. rated output power (W)
XSGxxxyyyyy, XSGxxxyyyyyzz, XSExxxyyyyy, XSExxxyyyyyzz, XSECxxxyyyyy, XSECxxxyyyyyzz	4.2-9.0	10000	90.0
	9.1-14.6	10000-11000	160.6
	14.7-17.0	10000	170.0
	17.1-19.0	10000	190.0

Note:

xxx=042-190, which denotes the rated output voltage from 4.2VDC to 19.0VDC; yyyyy=10000-11000, which denotes the rated output current from 10000mA to 11000mA; zz=AA-ZZ, It can be two uppercase English letters, which denotes for marketing purpose and not affect safety

Page 2 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 094747 0024 Rev. 00

Model No.	Rated output voltage (VDC)	Rated output current (mA)	Max. rated output power (W)
XSGxxxyyyy, XSGxxxyyyyzz, XSExxxyyyy, XSExxxyyyyzz, XSECxxxyyyy, XSECxxxyyyyzz	4.2-9.0	300-9999	90.0
	9.1-14.6	300-9999	146.0
	14.7-17.0	300-9999	170.0
	17.1-19.0	300-9999	190.0
	19.1-22.0	300-9500	190.0
	22.1-32.0	300-8500	205.8
	32.1-36.5	300-6000	219.0
	36.6-57.9	300-5000	210.0
	58.0-58.8	300-3600	210.2
	58.9-73.0	300-3400	204.0

Note:

xxx=042-730, which denotes the rated output voltage from 4.2VDC to 73.0VDC; yyyy=0300-9999, which denotes the rated output current from 300mA to 9999mA; zz=AA-ZZ, It can be two uppercase English letters, which denotes for marketing purpose and not affect safety.

Tested according to:

EN 61558-1:2005/A1:2009 EN 61558-2-16:2009/A1:2013

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.