



Product Service

CERTIFICATE

No. Z1A 094747 0134 Rev. 00

Holder of Certificate: **Xinsu Global Electronic Co., Limited**
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG

Certification Mark:



Product: **Switching power supply unit
(SWITCHING POWER SUPPLY/CHARGER)**

Tested according to: EN IEC 62368-1:2020/A11:2020
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 652102300201

Valid until: 2028-03-13

Date, 2023-03-14

(Rickyet Wang)

CERTIFICATE

No. Z1A 094747 0134 Rev. 00

Model(s): XSGxxxxxyyyy, XSExxxxxyyyy, XSECxxxxxyyyy,
XSGxxxxxyyyy, XSExxxxxyyyy, XSECxxxxxyyyy
(See below table for details.)

Brand Name: Xinsu Global



Parameters:

Rated Input: 100-240VAC, 50/60Hz, 3.0A Max

Rated Output: See below table for details

Protection Class: II

Degree of Protection: IP20

Model Name	Rated output voltage range (VDC)	Rated output current range (A)	Max. rated output power (W)
XSGxxxxxyyyy, XSExxxxxyyyy, XSECxxxxxyyyy	4.2-9.0	10.0	90.0
	9.1-14.6	10.0-11.0	160.6
	14.7-17.0	10.0	170.0
	17.1-19.0	10.0	190.0

Note:

xxx=042-190, which denotes the rated output voltage from 4.2VDC to 19.0VDC;

yyyyy=10000-11000, which denotes the rated output current from 10.0A to 11.0A.

Model Name	Rated output voltage range (VDC)	Rated output current range (A)	Max. rated output power (W)
XSGxxxxxyyyy, XSExxxxxyyyy, XSECxxxxxyyyy	4.2-9.0	0.30-9.999	90.0
	9.1-14.6	0.30-9.999	146.0
	14.7-17.0	0.30-9.999	170.0
	17.1-19.0	0.30-9.999	190.0
	19.1-22.0	0.30-9.500	190.0
	22.1-32.0	0.30-8.500	205.8
	32.1-36.5	0.30-6.000	219.0
	36.6-57.9	0.30-5.000	210.0
	58.0-58.8	0.30-3.600	210.2
	58.9-73.0	0.30-3.400	204.0

Note:

xxx=042-730, which denotes the rated output voltage from 4.2VDC to 73.0VDC;

yyyyy=0300-9999, which denotes the rated output current from 0.30A to 9.999A.