

ATTESTATION OF CONFORMITY

No. 22AE100557I008R1

The device bearing the trade name and model specified below has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified.

Report No. : E01A22100557I00801R1

Applicant : Xinsu Global Electronic Co., Limited

Address : Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road,
Central, HONG KONG

Manufacturer : Same as applicant

Address : Same as applicant

Description of Product : SWITCHING POWER SUPPLY/CHARGER

Model No. : XSGxxxxxyyyy, XSGxxxxxyyyyUS, XSExxxxxyyyy, XSExxxxxyyyyUS,
XSECxxxxxyyyy, XSECxxxxxyyyyUS, XSGxxxxxyyyy, XSGxxxxxyyyyUS,
XSExxxxxyyyy, XSExxxxxyyyyUS, XSECxxxxxyyyy, XSECxxxxxyyyyUS
(xxx, yyyy and yyyy are variables, see next page for detail.)

Trade Mark : 

Input Rating : 100-240VAC, 50/60Hz, 3.0A Max

Output Rating : 4.2-73.0VDC, 0.30-11.0A 219.0W Max

Test Standards : ICES-003 Issue 7



Tiger Xu
EMC Supervisor
Date of Issue: April 13, 2023

This attestation of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the production of the products.

Dongguan Anci Electronic Technology Co., Ltd.

Add.: 1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan Lake

Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

Web: www.gtgggroup.com E-mail: info@gtgggroup.com Tel:86-4007558988

Attachment

No. 22AE100557I008R1

Model Name	Rated output voltage range (VDC)	Rated output current range (A)	Max. rated output power (W)	Transformer (T1) type
XSGxxxxxyyyy, XSGxxxxxyyyyUS, XSExxxxxyyyy, XSExxxxxyyyyUS, XSECxxxxxyyyy, XSECxxxxxyyyyUS	4.2-9.0	10.0	90.0	TR-200-T1 XDH-E50-7575 E50 EE-50
	9.1-14.6	10.0-11.0	160.6	
	14.7-17.0	10.0	170.0	
	17.1-19.0	10.0	190.0	TR-200-T2 XDH-E50-7575 E50 EE-50
Note: xxx=042-190, which denotes the rated output voltage from 4.2VDC to 19.0VDC; yyyyy=10000-11000, which denotes the rated output current from 10.0A to 11.0A.				

Model Name	Rated output voltage range (VDC)	Rated output current range (A)	Max. rated output power (W)	Transformer (T1) type
XSGxxxxxyyyy, XSGxxxxxyyyyUS, XSExxxxxyyyy, XSExxxxxyyyyUS, XSECxxxxxyyyy, XSECxxxxxyyyyUS	4.2-9.0	0.30-9.999	90.0	TR-200-T1 XDH-E50-7575 E50 EE-50
	9.1-14.6	0.30-9.999	146.0	
	14.7-17.0	0.30-9.999	170.0	
	17.1-19.0	0.30-9.999	190.0	TR-200-T2 XDH-E50-7575 E50 EE-50
	19.1-22.0	0.30-9.500	190.0	
	22.1-32.0	0.30-8.500	205.8	
	32.1-36.5	0.30-6.000	219.0	TR-200-T3 XDH-E50-7575 E50 EE-50
	36.6-57.9	0.30-5.000	210.0	
	58.0-58.8	0.30-3.600	210.2	
	58.9-73.0	0.30-3.400	204.0	TR-200-T4 XDH-E50-7575 E50 EE-50
Note: xxx=042-730, which denotes the rated output voltage from 4.2VDC to 73.0VDC; yyyyy=0300-9999, which denotes the rated output current from 0.30A to 9.999A.				